



## PRODUCT INFORMATION



<b>Product Name:</b>	<b>ALUMINIUM WOOD PRIMER</b>
<b>Reference Number:</b>	7-5
<b>Coating Type:</b>	Alkyd resin with non-leafing aluminium.
<b>Typical Uses:</b>	Primer for all types of wood. Recommended for hardwoods.
<b>Colours Available:</b>	Aluminium.
<b>Appearance of Dried Film:</b>	Low sheen.
<b>Theoretical Coverage:</b>	8-12m <sup>2</sup> per litre depending on type of timber, porosity of timber etc.
<b>Surface Preparation:</b>	Ensure surface of timber is clean and dry.
<b>Application:</b>	Apply evenly by brush.  May also be applied by conventional spray. The addition of up to 15% Dacrylate Thinner R70 may be required to achieve optimum spray characteristics.
<b>Drying Time At 20°C: (Will Vary With Temperature, Air Movement etc.).</b>	<b>Touch Dry:</b> 2 hours. <b>Firm Dry:</b> 6 hours. <b>Overcoat:</b> Overnight.
<b>Packaging:</b>	500ml, 1 litre, 2.5 litre and 5 litre containers.
<b>Shelf Life:</b>	2 years in unopened containers, when stored under cover in good storage conditions.
<b>Storage:</b>	Under cover within temperature range of 5°C to 32°C.
<b>Clean-Up:</b>	Dacrylate Thinner R1 or R70.
<b>Health and Safety:</b>	Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

**Issued:** September 2001 SW/DAE/CR

