



## PRODUCT INFORMATION



<b>Product Name:</b>	<b>CLEAR LACQUER</b>
<b>Reference Number:</b>	8-15
<b>Coating Type:</b>	Modified chlorinated rubber.
<b>Typical Uses:</b>	Fast drying lacquer for wood, metal etc., also as a temporary protection against rusting for steel.
<b>Colours Available:</b>	Clear.
<b>Appearance of Dried Film:</b>	Full gloss.
<b>Volume Solids:</b>	27%.
<b>Theoretical Coverage:</b>	13.5m <sup>2</sup> per litre at 20 microns.
<b>Drying Time at 20°C: (Will vary with temperature, air movement etc.)</b>	<b>Touch Dry:</b> 20 minutes. <b>Firm Dry:</b> 90 minutes. <b>Overcoat:</b> 90 minutes.
<b>Packaging:</b>	5 litre containers.
<b>Shelf Life:</b>	2 years in unopened containers, when stored under cover in good storage conditions.
<b>Storage:</b>	Under cover within temperature range of 5°C to 32°C.
<b>Surface Preparation:</b>	Ensure substrate is clean and dry. Steel surfaces should be free of rust etc.
<b>Application:</b>	May be applied by brush, spray or dipping.
<b>Clean Up:</b>	Dacrylate Thinner R5.
<b>Health and Safety:</b>	Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

**Issued:** November 2001

SW/DAE/CR

