



## PRODUCT INFORMATION



<b>Product Name:</b>	<b>YACHT VARNISH</b>
<b>Reference Number:</b>	8-5
<b>Coating Type:</b>	Oleo-resinous.
<b>Uses/ Properties:</b>	Protection of external woodwork in industrial and marine environments. Suitable for hard and softwoods. Excellent water-resistance and durability.
<b>Appearance :</b>	Clear gloss.
<b>Surface preparation:</b>	Substrate must be clean, dry and free from grease, oil or other contaminants.
<b>Application:</b>	Apply 2-3 coats evenly by brush. (Thin <u>first</u> coat with 10-15% Dacrylate Thinner R1.) Ensure all edges, joints and open-end grain are adequately sealed.
<b>Coverage:</b>	Approximately 10-12 m <sup>2</sup> per litre.
<b>Drying Time at 20°C: (Will vary with temperature, air movement etc.)</b>	<b>Touch Dry:</b> 6-8 hours. <b>Firm Dry:</b> Overnight. <b>Overcoat:</b> Overnight.
<b>Packaging:</b>	2.5 litre, 1 litre and 500 ml containers.
<b>Shelf Life:</b>	2 years in unopened containers, when stored under cover in good storage conditions.
<b>Storage:</b>	Under cover within temperature range of 5°C to 32°C.
<b>Clean-Up:</b>	Dacrylate Thinner R1.
<b>Health and Safety:</b>	Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

**Issued:** November 2001                      SW/DAE/WHC/CR

