



PRODUCT INFORMATION



Product Name:	DAC CRETE 49SB SEALER
Reference Number:	49-1.
Coating Type:	Acrylic solution in organic solvent.
Typical Uses:	Transparent penetrating sealer for concrete and similar substrates, prior to application of Dac Crete 49SB Anti-Carbonation system.
Colours Available:	Clear (available with 'tracer' on request).
Theoretical Coverage:	Varies considerably depending on porosity of substrate, but typically in the range of 4-10m ² per litre.
Drying Time at 20°C: (Will vary with temperature, air movement etc.)	Touch Dry: 20 minutes. Firm Dry: 2 hours. Overcoat: 2 hours.
Packaging:	5 litre containers.
Shelf Life:	2 years in unopened containers, when stored under cover in good storage conditions.
Storage:	Under cover within temperature range of 5°C to 32°C.
Surface Preparation:	Remove all loose dust, friable material etc., to give a clean, dry substrate.
Application:	Apply by brush, ensuring complete coverage and penetration into crevices, rough profiles etc.
Clean Up:	Thinner R8.
Health and Safety:	Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

Issued: October 2001

SW/DAE/CR

