



# PRODUCT INFORMATION



<b>Product Name:</b>	<b>GLODAC OVERLACQUER</b>
<b>Reference Number:</b>	97-107
<b>Coating Type:</b>	Silicone alkyd.
<b>Typical Uses:</b>	As a protective lacquer for the Glodac range of fluorescent coatings to prolong colour and brightness on exterior exposure.
<b>Appearance of Dried Film:</b>	Clear, glossy.
<b>Theoretical Coverage:</b>	8-10m <sup>2</sup> per litre.
<b>Drying Time at 20°C: (Will vary with temperature, air movement etc.)</b>	<b>Touch Dry:</b> 1 hour. <b>Firm Dry:</b> 4 hours. <b>Overcoat:</b> N/A.
<b>Packaging:</b>	500 mls, 1 litre and 2.5 litre containers.
<b>Shelf Life:</b>	2 years in unopened containers, when stored under cover in good storage conditions.
<b>Storage:</b>	Under cover within temperature range of 5°C to 32°C.
<b>Surface Preparation:</b>	Apply to clean, dry Glodac colour.
<b>Application:</b>	Apply a thin coat evenly by brush or by conventional spray. Thin up to 20% with Dacrylate Thinner R70 for spraying.
<b>Clean Up:</b>	Dacrylate Thinner R1.
<b>Health and Safety:</b>	Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

**Issued:** November 2001

SW/DAE/CR