



## PRODUCT INFORMATION



<b>Product Name:</b>	<b>TENNIS COURT DRESSING</b>
<b>Reference Number:</b>	103-Line
<b>Coating Type:</b>	Water-borne acrylic slip resistant and smooth.
<b>Typical Uses:</b>	Hard wearing 'dressing' for tennis courts.
<b>Colours Available:</b>	Red - Ref: 103-4 (slip resistant) Ref: 103-54 (smooth) Green - Ref: 103-11 (slip resistant) Ref: 103-12 (smooth)
<b>Surface Preparation:</b>	Ensure surface is clean, dry and free from grease, moss, fungal growth etc. Make good any damaged or friable areas.
<b>Application:</b>	Brush or roller. (Unpainted substrates should be sealed first with the dressing thinned down with 10% water.)
<b>Application Rate:</b>	Approximately 8-10m <sup>2</sup> per litre.
<b>Drying Time at 20°C:</b> (Will vary with temperature, air movement etc.)	<b>Touch Dry:</b> 45 minutes. <b>Firm Dry:</b> 4 hours. <b>Overcoat:</b> 4 hours (foot traffic after 24 hours).
<b>Packaging:</b>	5 litre containers.
<b>Shelf Life:</b>	2 years in unopened containers, when stored under cover in good storage conditions.
<b>Storage:</b>	Under cover within temperature range of 5°C to 32°C. <u>Protect from frost.</u>
<b>Clean Up:</b>	Water.
<b>Health and Safety:</b>	Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

Issued: April 2005

KW/DAE/WHC

