



PRODUCT INFORMATION



Product Name	ACRYLACOTE PRIMER/UNDERCOAT
Reference Number	107-30
Coating Type	Vinyl acrylic co-polymer.
Typical Uses	Water thinnable primer/undercoat for wood, hardboard, MDF, chipboard, etc., for use with automatic vacuum coaters, with or without infra-red force drying. May be overcoated with emulsion or solvent-based decorative paints. Excellent opacity in single coat. Fast drying, supplied ready for use.
Colours Available	White (other colours to special minimum order).
Appearance Of Dried Film	Matt.
Application Rate	11 m ² per litre depending on porosity and texture of surface.
Drying Time At 20° C (Will Vary With Temperature, Air Movement, Etc)	Touch Dry: 20 minutes. Firm Dry: 2-3 hours. Overcoat: 3 hours with water-based decorative paints.
<u>Note:</u>	Drying times of water-based paints will vary widely depending upon humidity, air-movement, ventilation, etc.
Packaging	20 litre pails and 1000 litre IBC
Shelf Life	1 year or longer in unopened containers when stored under cover in good storage conditions.
Storage	Under cover within temperature range of 5°C to 32°C. <u>Protect from frost.</u>

Continued/



Surface Preparation

Ensure surface is clean and dry.

Treatment of Knots:

Water-based wood primers are essentially “self knotting”.

The fully dried Acrylacote Primer is unaffected by the resinous material in the knots (unlike oil-based primers which allow the resins in the timber to permeate through the film).

Timber which is heavily knotted should be spot-primed with the Acrylacote in the knotted areas and allowed to dry for at least 2 hours before overall painting.

Application

Automatic Vacuum Timber Coater (can also be applied by brush or spray).

Clean-Up

Clean equipment **IMMEDIATELY** with water.

Health And Safety

Please see relevant C.H.I.P. health and safety data sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc, based on this information. Dacrylate will not accept any claim for consequential or incidental damages.