




PRODUCT INFORMATION



Product Name:	DAC ROC SMOOTH MASONRY FINISH
Reference Number:	117-Line
Coating Type:	Acrylic/vinyl copolymer
Typical Uses:	Tough, durable coating for cement, brickwork, stucco etc., with added fungicide/algaecide.
Colours Available:	Limited range ex-stock. (Full range available to special order, may be subject to minimum order requirement.)
Appearance of Dried Film:	Low sheen finish.
Application Rate:	Approximately 8-10m ² per litre. (Note: Coverage will vary depending on porosity and texture of surface.)
Drying Time at 20°C: (Will vary with temperature, air movement etc.).	Touch Dry: 30 minutes. Firm Dry: 2 hours. Overcoat: 2 hours.
	Note: Drying times will vary depending on humidity, air-movement, etc.
Packaging:	5 litre containers.
Shelf Life:	2 years or longer in unopened containers when stored under cover in good storage conditions.
Storage:	Under cover within temperature range of 5°C to 32°C. <u>Protect from frost.</u>

Continued/

Surface Preparation:

Untreated Surfaces

Ensure surface is clean, dry and free from loose friable material.

Treat areas of heavy fungal growth with a 20% solution of household bleach, rinse well and dry-off. Porous substrates should be sealed with Dacrylate Masonry Sealer, ref:150-50.

Previously Painted Surfaces

Remove all loose, flaking materials and ensure existing coatings are sound and firm. Seal any exposed substrate with Dacrylate Masonry Sealer, ref:150-50.

Glossy surfaces should be lightly abraded and degreased prior to coating.

Two coats of Dac Roc are normally applied to suitably prepared and sealed surfaces.

Application:

May be applied by brush, roller or spray. For spray application, conventional or airless, the addition of 10-15% of water may be required to achieve optimum spray characteristics.

Clean-Up:

Water.

Note: Clean all equipment **IMMEDIATELY** after use – do not allow Dac Roc to dry.

Health and Safety:

Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.